

Declare.

LOCKING AND NON-LOCKING LADDER PULLS, PULLS IN 316L STAINLESS STEEL pba

Final Assembly: Tezze sul Brenta, Vicenza, Italy

Life Expectancy: 20 Year(s)

Embodied Carbon: 9.1 kg CO2 eq

Declared Unit: 1 kg

End of Life Options: Recyclable (100%)

Ingredients:

STEEL 1.4404 UNS S31603: Stainless steel AISI 316L; **STEEL 1.0715 UNS G12150:** Free-machining steel; **ZAMAK ZLO410 UNS Z35531:** Zinc casting alloy; **BRASS UNS C28500:** Brass; **ALUMINUM AW-6060 UNS A96060:** Aluminum alloy 6060; **STEEL 1.4305 UNS S30300:** Stainless steel; **STEEL 1.4301 UNS S30400:** Stainless steel; **POLYAMIDE PA6:** Polyamide; **STEEL:** Steel; **Powder coat:** Fatty acids, castor-oil, caustic-oxidized, distn. residues, esters with 1,3-butanediol; Barium sulfate; Titanium dioxide

Living Building Challenge Criteria: Compliant

I-13 Red List:

LBC Red List Free

% Disclosed: 100% at 100ppm

LBC Red List Approved

VOC Content: Not Applicable

Declared

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

PBA-0003

EXP. 01 AUG 2026

Original Issue Date: 2021