

# Declare.



## LOCKING AND NON-LOCKING LADDER PULLS, PULLS IN ALUMINUM pba

**Final Assembly:** Tezze sul Brenta, Vicenza, Italy

**Life Expectancy:** 20 Year(s)

**Embodied Carbon:** 5.92 kg CO2 eq

**Declared Unit:** 1 kg

**End of Life Options:** Recyclable (100%)

### Ingredients:

**ALUMINUM AW-6060 UNS A96060:** Aluminum alloy 6060; **ALUMINUM AW-6063 UNS A96063:** Aluminum alloy; **STEEL 1.0715 UNS G12150:** Free-machining steel; **ZAMAK ZLO410 UNS Z35531:** Zinc casting alloy; **STEEL 1.4404 UNS S31603:** Stainless steel AISI 316L; **BRASS UNS C28500:** Brass; **STEEL 1.4301 UNS S30400:** Stainless steel; **STEEL 1.4305 UNS S30300:** Stainless steel; **POLYAMIDE PA6:** Polyamide; **STEEL:** Steel; **Aluminum oxide:** Aluminum Oxide; **Powder coat:** Fatty acids, castor-oil, caustic-oxidized, distn. residues, esters with 1,3-butanediol; Barium sulfate; Titanium dioxide

**Living Building Challenge Criteria:** Compliant

### I-13 Red List:

- |   |                             |
|---|-----------------------------|
| <input checked="" type="checkbox"/> LBC Red List Free | % Disclosed: 100% at 100ppm |
| <input type="checkbox"/> LBC Red List Approved        | VOC Content: Not Applicable |
| <input type="checkbox"/> Declared                     |                             |

**I-10 Interior Performance:** Not Applicable

**I-14 Responsible Sourcing:** Not Applicable

PBA-0002

EXP. 01 AUG 2026

Original Issue Date: 2021